



November 1, 2006

Commercial & Workstation Monitors

Recommended End-user Prices (REP)

in euro (excl. VAT)



Hewlett-Packard Belgium BVBA/SPRL
Rue de l'Aéronef 1 – Luchtschipstraat 1
B-1140 Bruxelles - Brussel

Hewlett-Packard Luxembourg S.C.A.
7a, rue R. Stumper
L-2557 Luxembourg

© 2003 Hewlett-Packard Development Company, L.P.
Prices listed are for information purposes only, subject to change at
any time without notice and do not constitute any offer to sell.



Modifications to the Price List

	PN	Description	REP (in EUR) (Excl. VAT)	RC (in EUR) (Excl. VAT)
CRT Monitors				
Top Value	PF997AA#ABB	S7540 CRT 17" 1024 x 768@85Hz VGA TCO03 30 - 70 kHz	184,00 EUR	6,61 EUR
	PF997AT#ABB	S7540 CRT 17" 1024 x 768@85Hz VGA TCO03 30 - 70 kHz 17" Flat Square CRT / 0,24-0,28 mm Dot Pitch / Pixel Clock Speed 110 MHz Asset Control / Viewable Diag 40,6 cm (16") Horiz. Freq.: 30-70 KHz / Vert. Freq.: 50-160 Hz tilt range: 20° upward & 5° downward; Swivel range: 45° either side of center use controls: brightness, contrast, size & positioning, pincushion, trapezoid, parallelogram, moiré, degauss, factory reset/recall, current display mode. Max Power Rating 75 W / Power Save < 3 W / Weight 14 kg / Depth 43 cm Certifications: UL/CSA/CUL approval, ISO9241-3,-8 VDT guidelines approval, MPR-II compliant, TCO03, FCC approval, Microsoft WHQL certified, Energy Star compliant, CE Warranty : 3 years warranty on-site	119,00 EUR	6,61 EUR
LCD Monitors				
Top Value	PX848AA	HP L1506 LCD Monitor	189,00 EUR	4,96 EUR
	PX848AT	HP L1506 LCD Monitor Type Active matrix TFT (thin film transistor); Anti-glare and anti-static coatings Viewable image area 15 inches diagonal Viewing angle 130° horizontal, 100° vertical Brightness 250 nits Contrast ratio 450:1 Response rate 8 to 16 ms Dot/Pixel pitch 0.297 mm Colour depth support 16 million colours Frequency Horizontal frequency: 30 to 61 kHz, vertical frequency: 56 to 76 Hz Resolution 1024 x 768 @ 60 Hz (native) Input signal 15-pin D-sub (Analog VGA) Video cable Detachable 15-pin D-sub mini connector User controls (on- Base features Image control (auto, horizontal, vertical), positioning (vertical and horizontal), colour temperature (6500k, 9300k, custom), -5 to 30° vertical tilt, detachable base Graphics controller Genesis, MStar Power consumption 23 watts maximum, 21 watts typical 100 to 240 VAC, 50 to 60 Hz Power supply 2 watts Power Consumption, With stand: 34.0 x 20.3 x 35.5 cm, without Dimensions (W x D stand: 34.0 x 6.0 x 29.0 cm Weight 3.2 kg Options Optional HP Flat Panel Speaker Bar: the Speaker Bar attaches to the monitor's lower bezel to bring full audio support to select HP Monitors. Features dual speakers with full sound range and external jack for headphones, part number EE418AA Optional HP Compaq 7000 Series Ultra-slim Desktop Integrated Work Center Stand, optional: allows mounting of a 15, 17 or 19- Panel Monitor and an HP Compaq dc7100 or dc7600 Ultra-slim Desktop PC on a single stand for the convenience of an "all-in-one" part number DL641B. All sold separately Certifications, 9241-3, 7, 8 VDT guidelines, ISO 13406-2 pixel defect guidelines, MPR-II, CISPR, VCCI, CSA (Canada), ACA (Australia), TUV	169,00 EUR	4,96 EUR

N = New / P = Price Decrease / PI = Price Increase / D = Discontinued and available while supply lasts.

Prices are quoted in Euro (Excl. VAT and Excl. Recycling Contribution)



Commercial & Workstation Monitors 1/11/2006

	PN	Description	REP (in EUR) (Excl. VAT)	RC (in EUR) (Excl. VAT)
	Warranty	(German ergonomic), BSMI (Taiwan), CCC (China), MIC (South Korea), NOM (Mexico), Eastern European approvals, CE approval, Energy Star, TCO '03 (emissions, ergonomics, environment), Microsoft® Windows® certified (Microsoft® Windows® Microsoft® Windows® XP), UL listed, GOST (Russia), SASO (Saudi Arabia) Limited 3 years parts, labour and on-site service, including backlight. Availability varies by region. Certain restrictions and details, contact HP Customer Support or Service		


N = New / P = Price Decrease / PI = Price Increase / D = Discontinued and available while supply lasts.

Prices are quoted in Euro (Excl. VAT and Excl. Recycling Contribution)



Commercial & Workstation Monitors

1/11/2006

	PN	Description	REP (in EUR) (Excl. VAT)	RC (in EUR) (Excl. VAT)
PI Top Value 	PX849AA PX849AT	HP L1706 LCD Monitor EURO HP L1706 LCD Monitor EURO Type 17-inch Active Matrix TFT (thin film transistor) Viewable Image Area (diagonal) 17 in (43.2 cm) Screen Opening (W x H) 13.3 x 10.6 in (33.8 x 27.0 cm) Viewing Angle (typ)* 140 degrees horizontal/130 degrees vertical (10:1 minimum contrast ratio) Brightness (typ)* 300 nits (cd/m2) Contrast Ratio (typ)* 500 : 1 Response time * <12ms Pixel Pitch 0.264 mm Color Depth Support > 16 million colors Horizontal Frequency 30 to 83 kHz Vertical Frequency 50 to 76 Hz Graphics Controller Genesis, MStar, Realtec Native Resolution 1280 x 1024 @ 60 Hz (recommended) Maximum Resolution (Digital) N/A Preset VESA Graphic Modes (non interlaced) 1280 x 1024 @ 60 Hz and 75 Hz Input Signal 15 pin D-sub (Analog VGA)	199,00 EUR 169,00 EUR	4,96 EUR 4,96 EUR
	Top Value	PL766AT#ABB L1740 LCD 17" 17" Active Matrix TFT / 0.264 mm Pixel Pitch / Viewable Area 17" (43.2 cm) Anti-static / TCO 99 / VGA & DVI dual input / 500:1 Contrast Ratio / 300 nits Brightness <13 ms typical Response Rate / > 16.7 million Colors / 150° H, 135° V Viewing Angle / 140 MHz Pixel Clock Speed H Frequency: 30 to 83 kHz / Vertical Frequency: 56 to 76 kHz / Tilt: 35° up and 5° down / Swivel: +/-45° 90° Pivotal + software / Height adjustable 130mm range / 100 x 100 mm VESA pattern 1280 x 1024 (75 Hz); 1024 x 768 (75 Hz); 800 x 600 (75 Hz); 640 x 480 (75 Hz) Max Power rating < 60 W / Weight 7.0 kg / Kensington Lock-Ready 3 year Warranty parts and labor on-site HP / Silver & Carbonite	209,00 EUR	4,96 EUR
Top Value	EM869AA EM869AT	HP L1940T Flat Panel Monitor HP L1940T Flat Panel Monitor	279,00 EUR 259,00 EUR	4,96 EUR 4,96 EUR


N = New / P = Price Decrease / PI = Price Increase / D = Discontinued and available while supply lasts.

Prices are quoted in Euro (Excl. VAT and Excl. Recycling Contribution)



Commercial & Workstation Monitors

1/11/2006

	PN	Description	REP (in EUR) (Excl. VAT)	RC (in EUR) (Excl. VAT)
	Panel type Viewing angle Brightness Contrast ratio Response rate Pixel pitch Color depth support Frequency Native resolution Input signal Video cable User controls (on-screen display) Built-in power supply Weight Base features Options Certification and compliance Warranty	19-inch Active Matrix TFT (thin film transistor) Up to 140° horizontal/135° vertical (10:1 minimum contrast ratio) Up to 300 nits (cd/m2) Up to 500:1 8 ms (rise + fall) 0.294 mm > 16 million colors 30 to 83 kHz horizontal; 56 to 76 Hz vertical 1280 x 1024 @ 60 Hz (analog and digital) Two connectors: one 15-pin mini D-sub analog VGA and one DVI-D 15-pin D-sub mini connector; detached Size and positioning, contrast, brightness, clock, clock phase, selectable color temperature, serial number, mode displayed, sleep timer, input selection, factory reset Auto-ranging, 90 to 265 VAC; internal power supply Unpacked: 18.5 lb/8.4 kg; Packaged: 22.5 lb/10.2 kg Tilt range: -5° to + 35° vertical tilt, Horizontal swivel range: -170° to +170°, Pivot rotation: 90° into portrait orientation; Base: attached HP Compaq 7000 Series Ultra-slim Desktop Integrated Work Center Stand—Optional; mount an HP L1740 or L1940T monitor and an HP Compaq dc7600 Ultra-slim Desktop PC—Optional; powered directly by the monitor or PC, seamlessly attaches to the monitor's bezel; features dual speakers with full sound Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Three years parts, labor, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement options may include second business day on-site service, or r		
	Top Value PX850AT#ABB L1906 2T 19-inch FP TN Type Viewable Image Area (diagonal) Screen Opening (W x H) Viewing Angle (typ)* Brightness (typ)* Contrast Ratio (typ)* Response time * Pixel Pitch Color Depth Support	19-inch Active Matrix TFT (thin film transistor) 19 in (48.26 cm) 14.8 x 11.9 in (37.6 x 30.1 cm) 140 degrees horizontal/130 degrees vertical (10:1 minimum contrast ratio) 250 nits (cd/m2) 500 : 1 <12ms 0.264 mm > 16 million colors	209,00 EUR	4,96 EUR

N = New / P = Price Decrease / PI = Price Increase / D = Discontinued and available while supply lasts.

Prices are quoted in Euro (Excl. VAT and Excl. Recycling Contribution)





Commercial & Workstation Monitors

1/11/2006

	PN	Description	REP (in EUR) (Excl. VAT)	RC (in EUR) (Excl. VAT)
	Horizontal Frequency Vertical Frequency Graphics Controller Native Resolution Preset VESA Graphic Modes (non-interlaced) Input Signal Tilt Range Swivel Range Height Adjustable Pivot Rotation Base and Stand	30 to 83 kHz 50 to 76 Hz Genesis, MStar, Realtec 1280 x 1024 @ 60 Hz (recommended) 1280 x 1024 @ 60 Hz and 75 Hz 15 pin D-sub (Analog VGA) -5 to +30 degrees vertical tilt None No No Detachable		
Top Value	PH466AT#ABB	L1955 19" LCD Monitor (HP branded / Silver & Carbonite) 19" Active Matrix TFT / 0.294 mm Pixel Pitch / Viewable Area 19" (48.25 cm) Anti-glare / Anti-static / TCO 03 / VGA & DVI-I dual input / OSD / 1000:1 Contrast Ratio / > 250 nits Brightness < 16 ms typical Response Rate / 16.7 million Color Depth / 176° H, 176° V Viewing Angle / 140 MHz Pixel Clock Speed H Frequency: 30 to 82 kHz / V Frequency: 56 to 75 kHz / Tilt: 35° up and 5° down / Swivel: 50° left and 50° right 90° Pivotal / Height adjustable / 100 mm VESA 1280 x 1024 (75 Hz); 1024 x 768 (75 Hz); 800 x 600 (75 Hz); 640 x 480 (75 Hz); 720 x 400 (70 Hz) Max Power rating < 60 W / Weight 7.5 kg / Depth 201.1 cm with base 3 year Warranty parts and labor on-site	359,00 EUR	4,96 EUR

N = New / P = Price Decrease / PI = Price Increase / D = Discontinued and available while supply lasts.

Prices are quoted in Euro (Excl. VAT and Excl. Recycling Contribution)

	PN	Description	REP (in EUR) (Excl. VAT)	RC (in EUR) (Excl. VAT)
	F227AT#ABB	LP2065 20" LCD Monitor (HP branded / Silver & Carbonite) 20" Active Matrix TFT / 0.255 mm Pixel Pitch / Viewable Area 20.1" (51 cm) Anti-glare / Anti-static / TCO 03 / support for VGA & DVI-I via 2 connectors (2 x 2 types of cable included)/ OSD PiP (Picture in Picture capability) / 800:1 Contrast Ratio / 250 nits Brightness / 8 ms typical Response Rate (gray to gray) 16.7 million Color Depth / 178° H, 178° V Viewing Angle H Frequency: 30 to 94 kHz / V Frequency: 48 to 85 kHz / Tilt: 25° up & 5° down / Swivel: 45° up & 45° down 90° Pivotal / Height adjustable (13 cm) / 100 mm VESA / 1600 x 1200 (75 Hz); 1280 x 1024 (85 Hz); 1280 x 960 (60 Hz); 1152 x 900 (66 Hz); 1024 x 768 (85 Hz); 800 x 600 (85 Hz); 640 x 480 (85 Hz) Max Power rating < 75 W / Weight 9.2 kg / Depth 22 cm with base 3 year Warranty parts and labor on-site (or 48 hours direct unit replacement)	399,00 EUR	4,96 EUR
N / PROMO	EF224AT#ABB	LP2465 24" Wide Screen LCD Monitor (HP branded / Silver & Carbonite) 24" Active Matrix TFT / 0.270 mm Pixel Pitch / Viewable Area 24" (60,96 cm) Anti-glare / Anti-static / TCO 03 / 2 x DVI-I / OSD PiP (Picture in Picture capability) / 1000:1 Contrast Ratio / 500 nits Brightness / < 13 ms Response Rate 16.7 million Colors Depth / 178° H, 178° V Viewing Angle / 202 MHz Pixel Clock Speed H Frequency: 30 to 94 kHz / V Frequency: 48 to 85 Hz / Tilt: 25° up & 5° down / Swivel: 45° up & 45° down 90° Pivotal / Height adjustable (13 cm) / 100 mm VESA / 1920 x 1200 (60 Hz); 1600 x 1200 (75 Hz); 1280 x 1024 (85 Hz); 1280 x 960 (60 Hz); 1152 x 900 (66 Hz); 1024 x 768 (85 Hz); 800 x 600 (75 Hz); 640 x 480 (75 Hz) Max Power rating < 110 W / Weight 10.7 kg / Depth 23,2 cm with base 3 year Warranty parts and labor on-site	749,00 EUR	4,96 EUR
	DC198A	DVI monitor cable (for all DVI enabled flat panels)	19,00 EUR	
	DL641B	Integrated Work Center II	59,00 EUR	
	EE418AT	HP Stereo Speaker bar	20,00 EUR	

[Monitor arms for flat panels are available from Crea-Tech \(02/538.33.38\)](#)



Recycling Contribution

Since July 1st, 2001, all electrical and electronic equipment has been levied by a recycling contribution. This contribution is used for future environmental treatment of the equipment once the customer wants to dispose of it. HP has set up a transparent system that allows partners to invoice the contribution to their customers in a visible and easy manner.

This price list includes an additional column indicating the contribution per product. In the table mentioned beneath you will find the contribution (in Euro, VAT incl. and excl.).

Should you need more information with regards to the take back system, please do not hesitate to contact Recupel at 02/706 86 10 (www.recupel.be)

LEGEND TO RECYCLING CONTRIBUTION (RECUPEL)		
Products	VAT included	VAT excluded
Personal Computers	3 EUR	2,48 EUR
CRT Monitors	8 EUR	6,61 EUR
LCD Monitors	6 EUR	4,96 EUR
Laptops	2 EUR	1,65 EUR
Printers	2 EUR	1,65 EUR
Small IT	0,5 EUR	0,41 EUR